

Sikaflex®-201 US

One part polyurethane, elastomeric sealant/adhesive

Sales Quick Notes

Application

- Designed for all types of joints where maximum depth of sealant will not exceed 1/2 inch.
- Excellent for small joints and fillets, windows, door frames, reglets, flashing, common roofing detail applications, and many construction adhesive applications.
- Suitable for vertical and horizontal joints; readily placeable at 40°F.
- Has many applications as an elastic adhesive between materials with dissimilar coefficients of expansion.
- Submerged conditions, such as canal and reservoir joints.

Product Technology

- Sikaflex®-201 US is a premium-grade, high-performance, moisture-cured, 1-component, polyurethane-based, non-sag elastomeric sealant.
- Meets Federal specification TT-S-00230C, Type II, Class A. Meets ASTM C-920, Type S, Grade NS, Class 35, use T, NT, O, M, G, I; Canadian standard CAN/CGSB 19.13-M87.

Presentation - Benefits

- Eliminates time, effort, and equipment for mixing, filling cartridges, pre-heating or thawing, and cleaning of equipment.
- Fast tack-free and final cure times.
- High elasticity - cures to a tough, durable, flexible consistency with exceptional cut and tear-resistance.
- Excellent adhesion - bonds to most construction materials without a primer.
- Excellent resistance to aging, weathering.
- Proven in tough climates around the world.
- Paintable with water-, oil- and rubber based paints.
- Odorless, non-staining.
- Capable of $\pm 35\%$ joint movement.

Literature

- Product Data Sheet
- Material Safety Data Sheet

**Always refer to Current Product Data Sheet and MSDS for detailed performance specifications prior to use.*

Sealant Compatibility

- Test for adhesion, compatibility and staining
- Other sealant compatibility and adhesion issues must be addressed on a per customer application basis
- Please consult with Technical Service regarding specific applications where required at tsmh@us.sika.com

